

Product Categories

Thermostat Dehumidifier



Thermostat dehumidifier for
Laboratory, Workshop,
Warehouse, Electric room,
Library...



DJFT-1681E Thermostat Dehumidifier

- All-in-one machine control temperature and humidity
- Ducted connect to room
- Continuously drainage by external soft tube
- Automatic defrosting
- High efficiency, energy saving

Model no.	DJFT-1681E
Refrigerating capacity	7 Kw
Dehumidifying capacity	7 Kg/h
Heating capacity	4.8 Kw
Circulating air flow	2000 m ³ /h
Power supply	380V/50Hz
Rated power	2.82 Kw
Rated current	7.4 A
Sound level	<60 dB
Applying space	80~110 m ²
Air outlet pressure	150 Pa
Indoor unit dimension	600x405x1612mm
Outdoor unit dimension	N/A
Net weight	124 Kg
Gross weight	130 Kg

DJFT-2481E Thermostat Dehumidifier

- Running by multistage capacity adjustment based on real load capacity
- Various of control way with easy operation by touch screen
- Programmed control according to customer's requirement
- Unique design to separate the refrigerating system and air system
- Can be maintained and repaired when running, low malfunction rate.



Model no.	DJFT-2481E
Refrigerating capacity	12.5 Kw
Dehumidifying capacity	10 Kg/h
Heating capacity	6.4 Kw
Circulating air flow	2800 m ³ /h
Power supply	380V/50Hz
Rated power	4.9 Kw
Rated current	13.0 A
Sound level	<60 dB
Applying space	120~200 m ²
Air outlet pressure	150 Pa
Indoor unit dimension	890x650x1925mm
Outdoor unit dimension	845x910x850mm
Net weight	155 Kg
Gross weight	160 Kg

DJFT-3881E/4881E Portable Dehumidifier

- Running by multistage capacity adjustment based on real load capacity
- Various of control way with easy operation by touch screen
- Programmed control according to customer's requirement
- Unique design to separate the refrigerating system and air system
- Can be maintained and repaired when running, low malfunction rate.



Model no.	DJFT-3881E	DJFT-4881E
Refrigerating capacity	15 Kw	25 Kw
Dehumidifying capacity	15 Kg/h	20 Kg/h
Heating capacity	9.6 Kw	9.6 Kw
Circulating air flow	4000 m ³ /h	5600 m ³ /h
Power supply	380V/50Hz	380V/50Hz
Rated power	7.2 Kw	10 Kw
Rated current	19.0 A	26.3 A
Sound level	<70 dB	<70 dB
Applying space	200~280 m ²	280~350 m ²
Air outlet pressure	180 Pa	180 Pa
Indoor unit dimension	1350x860x1795mm	1350x860x1795mm
Outdoor unit dimension	1350x900x790mm	1350x900x790mm
Net weight	250 Kg	300 Kg
Gross weight	255 Kg	320 Kg



DJFT-7281E/9681E Thermostat Dehumidifier

- Running by multistage capacity adjustment based on real load capacity
- Various of control way with easy operation by touch screen
- Programmed control according to customer's requirement
- Unique design to separate the refrigerating system and air system
- Can be maintained and repaired when running, low malfunction rate.

Model no.	DJFT-7281E	DJFT-9681E
Refrigerating capacity	37.5 Kw	50 Kw
Dehumidifying capacity	30 Kg/h	40 Kg/h
Heating capacity	12.0 Kw	12.0 Kw
Circulating air flow	8000 m ³ /h	11200 m ³ /h
Power supply	380V/50Hz	380V/50Hz
Rated power	15 Kw	20 Kw
Rated current	39.5 A	52.6 A
Sound level	<70 dB	<70 dB
Applying space	350-500 m ³	500-650 m ³
Air outlet pressure	200 Pa	200 Pa
Indoor unit dimension	1650x500x1880mm	1650x500x1880mm
Outdoor unit dimension	1945x990x835mm	1945x990x835mm
Net weight	420 Kg	550 Kg
Gross weight	450 Kg	580 Kg